

Pallet Positioner

P3™ - Presto Pallet Positioner Load Leveler/Rotator

Model Number	Load Capacity	Raised Height	Lowered Height	Overall Base W / L	Turntable Diameter	Shipping Weight
Pallet Positioner						
P3	4500 lbs	30-1/2"	9-1/2"	36 x 48"	43-5/8"	615 lbs

Load and unload pallets without stooping, stretching, or walking

The P3 Presto Pallet Positioner automatically maintains pallets at a constant level and comfortable working height as layers of boxes are added or removed. Leveling is accomplished by a heavy-duty, reinforced rubber airbag that, once charged with shop air, can handle loads up to 4500 lbs. After airbag charging is complete, the P3 can be disconnected and moved to any location in the plant. Because the P3 is pneumatic, it can accommodate loads that vary substantially in weight (from 400 - 4500 lbs) so one unit is versatile enough to work in several areas.

The P3 - Presto Pallet Positioner features a turntable top with full 360° rotation. Anti-friction bearings for easy turning allow users to spin loads so they are always loading and unloading from the near side without having to walk around the unit.

Complete the system with a Presto Stacker for easy feeding and off-loading of the P3.



Available P3 Options:

- Plastic Cover: Keeps debris from falling through turntable
- Rotator Ring Disc Cover
- Solid Turntable Top: Accommodates small or odd-size pallets; Rectangular or Square Cover
- Ring Lock
- Bellows Guard: Prevents debris from collecting under unit

Presto P3's improve productivity and worker comfort in a wide variety of applications, including:

- Printing & Publishing**
- Graphic Arts**
- Metalworking**
- Woodworking**
- Machine Feeding or Off-loading**

Anywhere that pallet loads are built or broken down!

Accuload Positioner

Model Number	Load Capacity	Raised Height	Lowered Height	Overall Base W / L	Turntable Diameter	Shipping Weight
Accuload Series						
AL30	3000 lbs	30-1/4"	9-7/8"	24 x 48"	43"	500 lbs

Features

- 3000 lb holding capacity
- 1500 lb lifting capacity
- 21" vertical travel
- Foot control standard
- Optional pedestal control available
- Pressure relief valve standard
- 3/8" x 43" solid rotating platform
- Lifetime warranty on actuator
- Air requirements: 80 psi at 15 cfm
- Custom platforms available

Distributed By: Custom Equipment Company
 866-333-0728 919-847-5765 fax
 tom@custommhs.com www.custommhs.com



Yellow highlighted models are AIS (Always In Stock) and ship within one week.