2 Shelf Order Picking Carts

Model SO - Rugged general use carts with built in writing stand for record keeping

1,200 LB CAP.*(*800 lb with Thermorubber casters)



Options:

- 2 wheel brakes on swivel casters Code B5
- · All swivel casters Code AS
- Floor lock Code F5
- · Vinyl matting on top shelf Code VM
- Top shelf lips down (flush) Code FT
- Both shelves lips down (flush) Code FA
- Lockable drawer 5"h x 16"w x 16"d with 2 keys Code DS
- · Other heights available.

Product Features:

- All welded construction (except casters).
- Writing stand 12" by width of cart (4" above top shelf).
- Durable 12 gauge steel shelves, 3/16" thick angle corners, 12 gauge caster mounts, and tubular handle with smooth radius bend.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- 1-1/2" shelf lips up for retention.
- · Clearance between shelves 25".
- Overall height (excluding handle) 35".
- · Powder coated gray finish.

SPECIFICATIONS

WxL	5" Casters Models			Wgt.
(in)	Urethane	Thermorubber	Steel	(lbs)
18 x 30	S0130-U5	S0130-T5	S0130-L5	88
36	S0136-U5	S0136-T5	S0136-L5	96
48	S0148-U5	S0148-T5	S0148-L5	110
24 x 30	S0230-U5	S0230-T5	S0230-L5	106
36	S0236-U5	S0236-T5	S0236-L5	116
48	S0248-U5	S0248-T5	S0248-L5	136
60	S0260-U5	S0260-T5	S0260-L5	156
72	S0272-U5	S0272-T5	S0272-L5	178
30 x 36	S0336-U5	S0336-T5	S0336-L5	136
48	S0348-U5	S0348-T5	S0348-L5	162
60	S0360-U5	S0360-T5	S0360-L5	186
72	S0372-U5	S0372-T5	S0372-L5	210
36 x 48	S0448-U5	S0448-T5	S0448-L5	186
60	S0460-U5	S0460-T5	S0460-L5	214
72	S0472-U5	S0472-T5	S0472-L5	244

3 Shelf Order Picking Carts

Model LO - Rugged general use carts with built in writing stand for record keeping

1,200 LB CAP.*(*800 lb with Thermorubber casters)



Ontions

- 2 wheel brakes on swivel casters Code B5
- All swivel casters Code AS
- Floor lock Code F5
- Vinyl matting on top shelf Code VM
- Top shelf lips down (flush) Code FT
- All shelves lips down (flush) Code FA
- Other heights available.

Product Features:

- All welded construction (except casters).
- Writing stand 12" by width of cart (4" above top shelf).
- Durable 12 gauge steel shelves, 3/16" thick angle corners, 12 gauge caster mounts, and tubular handle with smooth radius bend.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement,
- 1-1/2" shelf lips up for retention.
- Clearance between shelves 12".
- Overall height (excluding handle) 35".
- · Powder coated gray finish.

Taller order picking carts see page 76

SPECIFICATIONS

WxL	5" Casters Models			Wgt.		
(in)	Urethane	Thermorubber	Steel	(lbs)		
18 x 30	L0130-U5	L0130-T5	L0130-L5	110		
36	L0136-U5	L0136-T5	L0136-L5	122		
48	L0148-U5	L0148-T5	L0148-L5	144		
24 x 30	L0230-U5	L0230-T5	L0230-L5	134		
36	L0236-U5	L0236-T5	L0236-L5	150		
48	L0248-U5	L0248-T5	L0248-L5	180		
60	L0260-U5	L0260-T5	L0260-L5	210		
72	L0272-U5	L0272-T5	L0272-L5	240		
30 x 36	L0336-U5	L0336-T5	L0336-L5	176		
48	L0348-U5	L0348-T5	L0348-L5	214		
60	L0360-U5	L0360-T5	L0360-L5	252		
72	L0372-U5	L0372-T5	L0372-L5	288		
36 x 48	L0448-U5	L0448-T5	L0448-L5	246		
60	L0460-U5	L0460-T5	L0460-L5	290		
72	L0472-U5	L0472-T5	L0472-L5	336		

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" \times 3" \times 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic
- Rubber
- Polyurethane
- Thermorubber
- · Steel (semi)
- Full Pneumatic
- · Semi Pneumatic

Brakes

Code

P6

R6

U6

T6

L6

8

Code

P8

R8

U8

T8

L8

Code

N8

N1

Z8

Mill

Code

MP

MS

Size (in)

6 x 2

6 x 2

6 x 2

6 x 2

6 x 2

8 x 2

8 x 2

8 x 2

8 x 2

8 x 2

Size (in)

8 x 3

12 x 4

8 x 3

N Series

Size (in)

Series

Pattern (in)

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

Duty Series

Bolt Hole

Pattern (in)

Pattern (in)

Bolt Hole

Pattern (in)

- Wing Brakes (Toe)
- Floor Lock

- Best rollability, high strength, hardest material.
- Best if floor has debris, quieter roll.
- Best if floor conditions vary, non-marking.
- Gray non-marking, soft rubber for quietest roll and best floor protection.
- High shock and impact resistant.
- Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Same as full pneumatic without maintenance of air.
- On swivel casters only, must be ordered with caster.
- Mount is welded in place, makes models not returnable.

Floor Lock



4 Series





Urethane Thermorubber

5 Series





Urethane Thermorubber





7, 6, & 8 Series





Mold On Rubber





Urethane

Thermorubber



Steel N Series





Full Pneumatic

Semi Pneumatic

Mill Duty Series





Phenolic

Steel

4.0	2.25.2.2			. ,			
4 5	eries—	Bolt Hole			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	Bearing	(set of 4)	Locks	Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4
5 S	eries—						
	01100	Bolt Hole			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	<u>Bearing</u>	(set of 4)	<u>Locks</u>	<u>Locks</u>
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5
7 S	eries—						
		Bolt Hole			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	<u>Bearing</u>	(set of 4)	<u>Locks</u>	<u>Locks</u>
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7
6 S	eries—	B. 11.11.1.			0		D 1
		Bolt Hole			Capacity	Floor	Brake

Bearing

Roller

Roller

Roller

Roller

Roller

Bearing

Roller

Roller

Roller

Roller

Roller

Bearing

Bearing

Roller

Ball

Ball

Ball

Ball

(set of 4)

4.800 lbs

2,000 lbs

3,600 lbs

2,200 lbs

4,000 lbs

Capacity

(set of 4)

4.800 lbs

2,400 lbs

3,800 lbs

2,400 lbs

4,000 lbs

Capacity

(set of 4)

1,200 lbs

2,200 lbs

2.000 lbs

Capacity

(set of 4)

7,000 lbs

7,000 lbs

Locks

F6

F6

F6

F6

F6

Floor

Locks

F8

F8

F8

F8

F8

Floor

Locks

FN

N/A

F8

Floor

Locks

ML

ML

Locks

B6

B6

B6

B6

B6

Brake

Locks

B8

B8

B8

B8

B8

Brake

Locks

BN

N/A

BN

Brake

Locks

BM

BM

Wheel Material

Polyurethane

Steel (semi)

Thermorubber

Wheel Material

Rubber (Mold-on)

Polyurethane

Steel (semi)

Thermorubber

Wheel Material

Full Pneumatic

Full Pneumatic

Semi Pneumatic

Wheel Material

Phenolic

Steel

Phenolic

Rubber (Mold-on)

Phenolic

Size (in)

8 x 2-1/2

8 x 2-1/2