

Job \_\_\_\_\_

# HD SUPER™ WORK CENTERS



## Dimensions

### Mobile Work Centers

30" (760mm) Wide

Cat. No.	Length		Post Material	Bottom Shelf Material (16 ga.)	Bottom 3-Sided Frame Material (16 ga.)	Bottom H-Frame Material (16 ga.)	Approx. Pkd. Wt.	
	(in.)	(mm)					(lbs.)	(kg)
MWT306FS	60	1525	SS	SS	—	—	134	61
MWT307FS	72	1825	SS	SS	—	—	152	69
MWT309FS	96	2439	SS	SS	—	—	182	83
MWT306FC	60	1525	Chrome	Galvanized	—	—	134	61
MWT307FC	72	1825	Chrome	Galvanized	—	—	152	69
MWT309FC	96	2439	Chrome	Galvanized	—	—	182	83
MWT306US	60	1525	SS	—	SS	—	117	53
MWT307US	72	1825	SS	—	SS	—	134	61
MWT309US	96	2439	SS	—	SS	—	163	74
MWT306HS	60	1525	SS	—	—	SS	117	53
MWT307HS	72	1825	SS	—	—	SS	133	60
MWT309HS	96	2439	SS	—	—	SS	163	74

**Load Ratings:** 60" long units-625 lbs. (283kg); 72" long units-750 lbs. (340 kg); 96" long units-1000 lbs. (454kg), equally distributed.

## Specifications

- **Top:** Seamless 14-gauge T-304 stainless steel, with 11-gauge channel support, nickel/chrome-plated after fabrication.
- **Bottom Shelf:** 16-gauge galvanized for T-304 stainless steel. 14-gauge available on special order. 30" x 60" (760 x 1525mm) work centers have 24" x 54" (610 x 1370mm) bottom shelves; 30" x 72" (760 x 1825mm) and 30" x 96" (760 x 2440mm) work centers have 24" x 60" (610 x 1525mm) bottom shelves.
- **Bottom Frame:** Three-sided tubular frame available in 16-gauge chrome-plated or stainless steel. 30" x 60" (760 x 1525mm) work centers have 24" x 54" (610 x 1370mm) bottom frames; 30" x 72" (760 x 1825mm) and 30" x 96" (760 x 2440mm) work centers have 24" x 60" (610 x 1525mm) bottom frames.
- **Posts:** Steel posts have an outside diameter of 1½" (38mm), with rolled grooves in 2" (51mm) increments along entire height.

Manufactured by:



Distributed by:  
**Custom Equipment Company**  
 866-333-0728  
 sales@custommhs.com  
 www.custommhs.com

L02-117  
 Rev. 11/00  
 Printed in U.S.A.

Information and specifications are subject to change without notice. Please confirm at time of order.