

Fixed & Adjustable Shelf Stock Trucks

Models CF, CZ, CG - Heavy duty trucks for warehouse, stockroom, & shipping

3,000 LB CAPACITY*(*2,000 lb with rubber casters)



Model CF Shown

3,000 LB CAPACITY*(*2,000 lb with rubber casters)



Model CZ Shown

1,200 LB CAPACITY*(*800 lb with rubber casters)



Model CG Shown

Product Features:

- All welded construction (except casters).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use (Models CF & CZ).
- **3/16" thick angle frame shelves with reinforced 13 gauge mesh decks**, except for solid 12 gauge bottom shelf. (Model CG only).
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- 1-1/2" shelf lips up for retention - (only bottom shelf for Model CZ).
- **Adjustable middle shelf** is standard - adjustable on 3-1/2" centers - (Model CZ only).
- Model CZ - Adjustable shelf is flush only.
- Clearance between shelves - Model CF - 11", Model CG - 13".
- Overall height - Model CF - 72", Model CZ - 57", Model CG - 67".
- Powder coated gray finish.

Options:

- 2 wheel brakes on swivel casters - **Code B5 or B6**
- Floor lock - **Code F5 or F6**
- All shelves lips down - **Code FA**
- Additional adjustable shelves - **Code AT** (Model CZ only)

Model CF - 6 Shelf

WxL (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
18 x 36	CF136-P6	CF136-R6	CF136-U6	220
48	CF148-P6	CF148-R6	CF148-U6	266
24 x 36	CF236-P6	CF236-R6	CF236-U6	266
48	CF248-P6	CF248-R6	CF248-U6	326
60	CF260-P6	CF260-R6	CF260-U6	384
72	CF272-P6	CF272-R6	CF272-U6	444
30 x 36	CF336-P6	CF336-R6	CF336-U6	312
48	CF348-P6	CF348-R6	CF348-U6	384
60	CF360-P6	CF360-R6	CF360-U6	456
72	CF372-P6	CF372-R6	CF372-U6	528
36 x 48	CF448-P6	CF448-R6	CF448-U6	442
60	CF460-P6	CF460-R6	CF460-U6	528
72	CF472-P6	CF472-R6	CF472-U6	598

Model CZ - Adjustable Shelf

WxL (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
24 x 36	CZ236-P6	CZ236-R6	CZ236-U6	176
48	CZ248-P6	CZ248-R6	CZ248-U6	198
60	CZ260-P6	CZ260-R6	CZ260-U6	218
72	CZ272-P6	CZ272-R6	CZ272-U6	240
30 x 48	CZ348-P6	CZ348-R6	CZ348-U6	224
60	CZ360-P6	CZ360-R6	CZ360-U6	248
72	CZ372-P6	CZ372-R6	CZ372-U6	274
36 x 48	CZ448-P6	CZ448-R6	CZ448-U6	250
60	CZ460-P6	CZ460-R6	CZ460-U6	280
72	CZ472-P6	CZ472-R6	CZ472-U6	308

Model CG - Visual 5 Shelf

WxL (in)	5" Casters Models			Wgt. (lbs)
	Urethane	Thermorubber	Steel	
24 x 36	CG236-U5	CG236-T5	CG236-L5	198
48	CG248-U5	CG248-T5	CG248-L5	228
30 x 48	CG348-U5	CG348-T5	CG348-L5	254
60	CG360-U5	CG360-T5	CG360-L5	300

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic
 - Best rollability, high strength, hardest material.
- Rubber
 - Best if floor has debris, quieter roll.
- Polyurethane
 - Best if floor conditions vary, non-marking.
- Thermorubber
 - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi)
 - High shock and impact resistant.
- Full Pneumatic
 - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic
 - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe)
 - On swivel casters only, must be ordered with caster.
- Floor Lock
 - Mount is welded in place, makes models not returnable.

4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

Floor Lock



4 Series



Urethane Thermorubber

5 Series



Urethane Thermorubber



Steel

7, 6, & 8 Series



Phenolic

Mold On Rubber



Urethane

Thermorubber



Steel


N Series



Full Pneumatic

Semi Pneumatic

Mill Duty Series



Phenolic

Steel