

2 Shelf Ergonomic Handle Service Carts

Model ES - Comfortable ergonomic handle transporters

1,200 LB CAP.*(*800 lb with Thermorubber casters)



Options:

- 2 wheel brakes on swivel casters - **Code B5**
- All swivel casters - **Code AS**
- Floor lock - **Code F5**
- Top shelf lips down (flush) - **Code FT**
- Both shelves lips down (flush) - **Code FA**
- Lockable drawer 5"h x 16"w x 16"d with 2 keys - **Code DS**
- Vinyl matting on top shelf - **Code VM**
- Other heights available.

Product Features:

- All welded construction (except casters).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- **Ergonomic tubular handle** (4" above top shelf) with smooth radius bend.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- 1-1/2" shelf lips up for retention.
- Clearance between shelves - 25".
- Overall height (excluding handle) - 35".
- Powder coated gray finish.

SPECIFICATIONS

WxL (in)	5" Casters Models			Wgt. (lbs)
	Urethane	Thermorubber	Steel	
18 x 36	ES136-U5	ES136-T5	ES136-L5	90
48	ES148-U5	ES148-T5	ES148-L5	104
24 x 30	ES230-U5	ES230-T5	ES230-L5	98
36	ES236-U5	ES236-T5	ES236-L5	108
48	ES248-U5	ES248-T5	ES248-L5	128
60	ES260-U5	ES260-T5	ES260-L5	146
72	ES272-U5	ES272-T5	ES272-L5	168
30 x 36	ES336-U5	ES336-T5	ES336-L5	124
48	ES348-U5	ES348-T5	ES348-L5	150
60	ES360-U5	ES360-T5	ES360-L5	174
72	ES372-U5	ES372-T5	ES372-L5	198
36 x 48	ES448-U5	ES448-T5	ES448-L5	172
60	ES460-U5	ES460-T5	ES460-L5	200
72	ES472-U5	ES472-T5	ES472-L5	230

2 Shelf Ergonomic Handle Vibration Reduction Carts

Model LR - Ergonomic handle vibration reduction transporters

1,200 LB CAPACITY



Options:

- 2 wheel brakes on swivel casters - **Code BN**
- All swivel casters - **Code AS**
- Floor lock - **Code F8 or FN**
- Top shelf lips down (flush) - **Code FT**
- Both shelves lips down (flush) - **Code FA**
- Lockable drawer 5"h x 16"w x 16"d with 2 keys - **Code DS**
- Vinyl matting on top shelf - **Code VM**
- Other heights available.

Product Features:

- All welded construction (except casters).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- **Ergonomic tubular handle** (4" above top shelf) with smooth radius bend.
- Bolt on casters, 2 swivel & 2 rigid for easy replacement.
- 1-1/2" shelf lips up for retention.
- Clearance between shelves - 25".
- Overall height (excluding handle) - 39".
- Powder coated gray finish.

SPECIFICATIONS

WxL (in)	8" Pneumatic Casters		
	Semi Models	Full Models	Wgt.(lbs)
24 x 30	LR230-Z8	LR230-N8	122
36	LR236-Z8	LR236-N8	132
48	LR248-Z8	LR248-N8	152
60	LR260-Z8	LR260-N8	172
72	LR272-Z8	LR272-N8	194
30 x 36	LR336-Z8	LR336-N8	150
48	LR348-Z8	LR348-N8	174
60	LR360-Z8	LR360-N8	200
72	LR372-Z8	LR372-N8	224
36 x 48	LR448-Z8	LR448-N8	196
60	LR460-Z8	LR460-N8	226
72	LR472-Z8	LR472-N8	256

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic
 - Best rollability, high strength, hardest material.
- Rubber
 - Best if floor has debris, quieter roll.
- Polyurethane
 - Best if floor conditions vary, non-marking.
- Thermorubber
 - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi)
 - High shock and impact resistant.
- Full Pneumatic
 - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic
 - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe)
 - On swivel casters only, must be ordered with caster.
- Floor Lock
 - Mount is welded in place, makes models not returnable.

4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

Floor Lock



4 Series



Urethane Thermorubber

5 Series



Urethane Thermorubber



Steel

7, 6, & 8 Series



Phenolic Mold On Rubber




Urethane Thermorubber



Steel

N Series



Full Pneumatic Semi Pneumatic

Mill Duty Series



Phenolic Steel