# jescohuskydumper,





### JescoHuskyDumper® Self Dumping Hoppers

Over 60 models to select from! Standard units narrow, low profile, large volume, and if you don't find one to fit your application just tell us because we manufacture specials!

All-welded self dumping hoppers handle bulk materials and scrap generated from manufacturing processes. These units can be moved with a forklift or rolled on optional casters. Forklift of proper capacity rating must be used to empty the hopper. The narrow models are designed to fit into tight spaces without losing load capacity and may be shipped two wide and stacked in a truck. Trip handle is one piece with a positive locking mechanism. Jesco's dumpers are engineered to dump when the locking handle is tripped and will return to the upright locked position when empty. Units are designed to empty when

filled up the sloped front to shift the center of gavity towards the mouth of the unit.

Safety retaining chain and trip rope assembly are standard on all hoppers manufactured. Painted Vista Green but optional color choices are available.

Packaging is optional but may be added for an extra cost.

Warning: Always observe all safety rules of your company, OSHA, ASME, ITA, along with the manufacturer of the forklift. Dumpers are to be used by properly trained personnel only. Operational video is available on the website.

If your existing Jesco hoppers are missing their yellow safety labels call 1-800-609-8289 and they will be replaced at no charge. Limit is 3.

Please read the "Operational and Maintenance" sheet which accompanies each shipment. Your company's PM should include hopper inspections for excessive wear and tear.

## **Standard Features:**

- Safety retaining chain
- Remote trip rope assembly
- Safety labels

- Safety latch
- Vista green color

## **Optional Features:**

- Casters for units up to 21/2 cu. yards
- Lids 1 to 2<sup>1</sup>/<sub>2</sub> cu. yards
- Paint colors: Red, OSHA blue, Black, Light gray, Dark gray, Orange, Yellow.
- · Glass recycling hood
- False bottom
- Outrigger base



- 3-Way entry
- Bolt on casters
- · Left hand release
- Gate valve
- Drain plug
- Drain hole
- Lifting lugs
- 100% water tight



**Rights Itself** 

- 2 -



Safety retaining chain and trip rope store conveniently on the back of the unit when not in use.



For More Information: 866-333-0728



## Heavy Duty Formed Base

12 gauge body

8 gauge base

Stackable 3 high empty



<sup>1</sup>/<sub>3</sub> cu. yd. shown

Part No	Capacity	Dimensions	Fork Openings	Weight
211701	.25 cu. yd / 2000 lbs	49"L x 30 <sup>3</sup> /4"W x 26 <sup>1</sup> /2"H	2 <sup>1</sup> /2" x 8 <sup>1</sup> /2" x 20" OC	305 lbs
211705	.33 cu. yd / 2000 lbs	48 <sup>1</sup> /2"L x 30 <sup>3</sup> /4"W x 31 <sup>1</sup> /2"H	2 <sup>1</sup> /2" x 8 <sup>1</sup> /2" x 20" OC	315 lbs
211711	.50 cu. yd / 2000 lbs	48 <sup>1</sup> /2"L x 41 <sup>1</sup> /2" x "W x 31 <sup>1</sup> /2"H	2 <sup>1</sup> / <sub>2</sub> " x 11" x 30" OC	365 lbs
211731	1.0 cu. yd / 2000 lbs	62"L x 411/2"W x 37"H	2 <sup>1</sup> / <sub>2</sub> " x 11" x 30" OC	445 lbs
211741	1.5 cu. yd / 2000 lbs	62"L x 591/2"W x 37"H	2 <sup>1</sup> / <sub>2</sub> " x 14" x 48" OC	540 lbs
211751	2.0 cu. yd / 2000 lbs	64"L x 591/2"W x 46"H	2 <sup>1</sup> / <sub>2</sub> " x 14" x 48" OC	600 lbs
211761	2.5 cu. yd / 2000 lbs	64"L x 591/2"W x 51"H	2 <sup>1</sup> / <sub>2</sub> " x 14" x 48" OC	620 lbs
*211771	3.0 cu. yd / 2000 lbs	71 <sup>1</sup> /2"L x 65 <sup>1</sup> /2"W x 59 <sup>1</sup> /2"H	2 <sup>1</sup> / <sub>2</sub> " x 9 <sup>1</sup> / <sub>2</sub> " x 39" OC	810 lbs
*211781	4.0 cu. yd / 2000 lbs	71 <sup>1</sup> /2"L x 85 <sup>1</sup> /2"W x 59 <sup>1</sup> /2"H	2 <sup>1</sup> /2" x 9 <sup>1</sup> /2" x 39" OC	970 lbs

\* Not stackable, casters not recommended. Non stock item, manufactured to order.

## Extra Heavy Duty Formed Base

10 gauge body

8 gauge base Stackable 3 high empty



1 cu. yd. shown

Part No Capacity **Dimensions** Fork Openings Weight 21/2" x 11" x 30" OC 211531 1.0 cu. yd / 4000 lbs 62"L x 41<sup>1</sup>/<sub>2</sub>"W x 37"H 495 lbs 211541 1.5 cu. yd / 4000 lbs 62"L x 591/2"W x 37"H 21/2" x 14" x 48" OC 630 lbs 211551 2.0 cu. yd / 4000 lbs 64"L x 591/2"W x 46"H 21/2" x 14" x 48" OC 705 lbs 64"L x 59<sup>1</sup>/2"W x 51"H 211561 2.5 cu. yd / 4000 lbs 21/2" x 14" x 48" OC 750 lbs 71<sup>1</sup>/2"L x 65<sup>1</sup>/2"W x 59<sup>1</sup>/2"H \*211571 3.0 cu. yd / 4000 lbs 2<sup>1</sup>/<sub>2</sub>" x 9<sup>1</sup>/<sub>2</sub>" x 39" OC 970 lbs 4.0 cu. yd / 4000 lbs 21/2" x 91/2" x 39" OC \*211581 71<sup>1</sup>/<sub>2</sub>"L x 85<sup>1</sup>/<sub>2</sub>"W x 59<sup>1</sup>/<sub>2</sub>"H 1070 lbs

\* Not stackable, casters not recommended. Non stock item, manufactured to order.

## Super Heavy Duty Formed Base

7 gauge body Base: 8 gauge (1/4-1/2 yd.) / .220 gauge (3/4-21/2 yd.) Stackable 3 high empty



2 cu. yd. shown

Part No	Capacity	Dimensions	Fork Openings	Weight
211301	.25 cu. yd / 4000 lbs	49"L x 30 <sup>3</sup> /4"W x 26 <sup>1</sup> /2"H	2 <sup>1</sup> / <sub>2</sub> " x 8 <sup>1</sup> / <sub>2</sub> " x 20" OC	375 lbs
211305	.33 cu. yd / 4000 lbs	48 <sup>1</sup> /2"L x 30 <sup>3</sup> /4"W x 31 <sup>1</sup> /2"H	2 <sup>1</sup> / <sub>2</sub> " x 8 <sup>1</sup> / <sub>2</sub> " x 20" OC	405 lbs
211311	.50 cu. yd / 4000 lbs	48 <sup>1</sup> /2"L x 41 <sup>1</sup> /2"W x 31 <sup>1</sup> /2"H	2 <sup>1</sup> / <sub>2</sub> " x 11" x 30" OC	470 lbs
211321	.75 cu. yd / 5000 lbs	56 <sup>3</sup> /4"L x 41 <sup>1</sup> /2"W x 35 <sup>1</sup> /2"H	2 <sup>1</sup> / <sub>2</sub> " x 11" x 30" OC	575 lbs
211331	1.0 cu. yd / 6000 lbs	62"L x 411/2"W x 37"H	2 <sup>1</sup> /2" x 11" x 30" OC	625 lbs
211341	1.5 cu. yd / 6000 lbs	62"L x 591/2"W x 37"H	2 <sup>1</sup> / <sub>2</sub> " x 11" x 48" OC	785 lbs
*211346	1.5 cu. yd / 6000 lbs	64"L x 461/2"W x 46"H	2 <sup>1</sup> / <sub>2</sub> " x13 <sup>1</sup> / <sub>2</sub> " x 35" OC	780 lbs
211351	2.0 cu. yd / 6000 lbs	64"L x 591/2"W x 46"H	2 <sup>1</sup> / <sub>2</sub> " x 14" x 48" OC	880 lbs
*211356	2.0 cu. yd / 6000 lbs	64"L x 461/2"W x 51"H	2 <sup>1</sup> / <sub>2</sub> " x 13 <sup>1</sup> / <sub>2</sub> " x 35" OC	790 lbs
211361	2.5 cu. yd / 6000 lbs	64"L x 59¹/₂"W x 51"H	2 <sup>1</sup> / <sub>2</sub> " x 14" x 48" OC	905 lbs

\* Narrow model. Non stock item, manufactured to order.



## Super Extra Heavy Duty Structural Base

7 Gauge Body

1/4" Base

Non-stackable

Non stock item, manufactured to order



Part No	Capacity	Dimensions	Fork Openings	Weight
211332	1.0 cu. yd / 6000 lbs	62"L x 411/2"W x 37"H	3" x 111/4" x 30" OC	660 lbs
211342	1.5 cu. yd / 6000 lbs	62"L x 591/2"W x 37"H	3" x 111/4" x 30" OC	820 lbs
211352	2.0 cu. yd / 6000 lbs	64"L x 591/2"W x 46"H	3" x 111/4" x 30" OC	905 lbs
211362	2.5 cu. yd / 6000 lbs	64"L x 59¹/₂"W x 51"H	3" x 111/4" x 30" OC	930 lbs

### Large Volume Super Heavy Duty Structural Base

7 gauge body

Base: <sup>1</sup>/<sub>4</sub>" (3-6 yd.) / <sup>3</sup>/<sub>8</sub>" (8-10 yd.)

Non-stackable

Non stock item, manufactured to order



1	Part No	Capacity	Dimensions	Fork Openings	Weight
	**211371	3 cu. yd / 6000 lbs	71 <sup>1</sup> /2"L x 65 <sup>1</sup> /2"W x 59 <sup>1</sup> /2"H	3" x 10" x 39" OC	1250 lbs
	**211381	4 cu. yd / 6000 lbs	71 <sup>1</sup> /2"L x 85 <sup>1</sup> /2"W x 59 <sup>1</sup> /2"H	3" x 10" x 39" OC	1385 lbs
	**211391	5 cu. yd / 6000 lbs	71 <sup>1</sup> /2"L x 105 <sup>1</sup> /2"W x 59 <sup>1</sup> /2"H	3" x 10" x 39" OC	1560 lbs
	*211411	6 cu. yd / 6000 lbs	71 <sup>1</sup> /2"L x 125 <sup>1</sup> /2"W x 59 <sup>1</sup> /2"H	3" x 10" x 39" OC	1650 lbs
	*211431	8 cu. yd / 10000 lbs	91"L x 109"W x 70"H	3" x 10" x 50" OC	3000 lbs
	*211451	10 cu. yd / 10000 lbs	91"L x 135"W x 70"H	3" x 10" x 50" OC	3500 lbs
	* Contoro	not ovoilable ** Crooic	have required for use with ear	stora Saa naga E	

Casters not available. Special base required for use with casters. See page 5.

## Low Profile

Super Heavy Duty Formed Base

7 gauge body

8 gauge base

Stackable 3 high empty

Non stock item, manufactured to order



. (	Part No	Capacity	Dimensions	Fork Openings	Weight
	+212299	.125 cu. yd / 2000 lbs	30"L x 281/2"W x 17"H	2 <sup>1</sup> / <sub>2</sub> " x 7 <sup>1</sup> / <sub>2</sub> " x 18" OC	210 lbs
	+212301	.25 cu. yd / 4000 lbs	30"L x 411/2"W x 17"H	2 <sup>1</sup> / <sub>2</sub> " x 10 <sup>3</sup> / <sub>4</sub> " x 29 <sup>1</sup> / <sub>2</sub> " OC	260 lbs
	+212305	.33 cu. yd / 4000 lbs	44"L x 411/2"W x 24"H	2 <sup>1</sup> / <sub>2</sub> " x 10 <sup>3</sup> / <sub>4</sub> " x 29 <sup>1</sup> / <sub>2</sub> " OC	370 lbs
	*212311	.5 cu. yd / 4000 lbs	44"L x 491/2"W x 24"H	2 <sup>1</sup> / <sub>2</sub> " x 10 <sup>3</sup> / <sub>4</sub> " x 29 <sup>1</sup> / <sub>2</sub> " OC	410 lbs
	* Not stac	kable. * Base is wider th	an body		

For More Information: 866-333-0728

## Large Volume, Low Profile Super Heavy Duty Structural Base

7 gauge body

 $1/_4$ " base Non-stackable Non stock item, manufactured to order



Wide body design and convenient working height of 46" make these units naturals for handling large, long bulky items. Lids not available.

Part No	Capacity	Dimensions	Fork Openings	Weight
**212361	2.5 cu. yd / 6000 lbs	64"L x 671/2"W x 46"H	3" x 10 <sup>1</sup> /2" x 39" OC	995 lbs
**212371	3.0 cu. yd / 6000 lbs	64"L x 871/2"W x 46"H	3" x 10 <sup>1</sup> /2" x 39" OC	1085 lbs
**212376	3.5 cu. yd / 6000 lbs	64"L x 1011/2"W x 46"H	3" x 10 <sup>1</sup> / <sub>2</sub> " x 39" OC	1225 lbs

\*\* Special base required for use with casters. See page 5.

# jescohuskydumper.

## Lids

Lids are optional on units up to  $2\frac{1}{2}$  cubic yard capacity. These units help in meeting environmental regulations and insurance codes. Contents of hoppers stay out of sight for a neater appearance at your facility.

Two piece lids are available for 1 cu. yd. through 21/2 cu. yd. capacity hoppers. Lids not available on low profile or narrow hoppers.

Options: Padlock hasp, dust collars.

14 gauge material. Painted Vista Green.

### Specify type A or type C lid.

	Hopper	
Part No	Capacity	Weight
220044	1.0 cu. yd.	65 lbs
220054	1.5 cu. yd.	92 lbs
220064	2.0 cu. yd.	106 lbs
220074	2.5 cu. yd.	106 lbs



Type A Front half opens only



Type C Both halves open



## **Caster Options**

Hoppers with casters are easy to roll. Available in Semi Steel (SS), Phenolic (PH), Polyurethane (PU), or Moldon Rubber (MR). Casters provide mobility on most surfaces.

Other caster options available.


Casters are welded to base of hoppers unless otherwise specified.

Capacity must match or exceed capacity of hopper.

Part No	Dimensions	Material	Capacity	Weight
240211	6" Dia. x 2" W	SS	4800 lbs	34 lbs
240221	6" Dia. x 2" W	PU	4800 lbs	37 lbs
240231	6" Dia. x 2" W	PH	4000 lbs	28 lbs
240251	6" Dia. x 2" W	MR	2000 lbs	28 lbs
240321	6" Dia. x 21/2" W	PU	6000 lbs	50 lbs
240351	6" Dia. x 21/2" W	MR	2400 lbs	38 lbs
240311	6" Dia. x 21/2" W	SS	6000 lbs	51 lbs
240331	6" Dia. x 21/2" W	PH	6000 lbs	37 lbs
240421	8" Dia. x 2" W	PU	4800 lbs	56 lbs
240451	8" Dia. x 2" W	MR	2400 lbs	43 lbs
240511	8" Dia. x 21/2" W	SS	6000 lbs	61 lbs
240531	8" Dia. x 21/2" W	PH	6000 lbs	46 lbs
240541	8" Dia. x 21/2" W	PU	6000 lbs	77 lbs

## Special Bases Required When Ordering Casters On Certain Hoppers

Hoppers marked with **two asterisks (\*\*)** require special bases (part no. 230600) in order to be equipped with casters. These special bases are in addition to the price of the hopper, as are the casters. Contact a sales representative for further information and pricing.





## **Glass Recycling Hood**

Glass recycling hoods are available for recycling centers or to give solar and glass manufacturing facilities a place for their non-conforming products. Provides a cleaner way to keep shards in your dumper and off manufacturing floor. These hoods are factory installed on the hopper of your choice. May require addition of counterweights (also factory installed). 7 gauge steel.

Manufactured to order.

Part No	For Hopper Capacity
220100	.25 cu. yd. to 1 cu. yd.
220110	1.5 cu. yd. to 2.5 cu. yd.

## False Bottoms

Used inside the hopper for processes that use lubricating or cooling fluids (CNC Machines, screw machines etc.) and need to separate the shavings or solids from the liquids. To be used with drain plug (230145) or drain gate valve 1" (230140), both at additional cost. Twelve  $1/_8$ " diameter staggered holes in a 11 gauge sheet bolted to an angle frame to allow access for cleaning under the false bottom. Manufactured to order.

e lubricating ines etc.) and		
he liquids.	-	
ate valve 1"		
ameter 📉 📉	Part No	For Hopper Capacity
	Part No 230135	For Hopper Capacity .25 cu. yd. to 2.5 cu. yd.