


Spill-Control Platforms

- Heavy-gauge steel construction
- Removable welded steel bar grating
- Ramps available in two heights: 6-1/2" and 12"
- Helps comply with EPA and OSHA requirements
- Models with 66 and 99 gallon capacity help comply with Uniform Fire Code



**Model
SSB-5176**

**Model
SSB-5151**




**Model
SSB-5125**

Low-Profile Models

	SUMP CAP.	DIMENSIONS W x L x H	Model No.	Ship Wt.	Capacity Lbs. UDL
2-Drum	33 gal.	51 x 26 x 6.5	SSB-5125	125	3000
2-Drum	66 gal.	51 x 26 x 12	SSB-5125-66	158	3000
4-Drum	66 gal.	51 x 51 x 6.5	SSB-5151	233	6000
6-Drum	99 gal.	76 x 51 x 6.5	SSB-5176	358	9000
Ramp*	—	33 x 36 x 6.5	SSB-RAMP	70	1500

*Ramp not for use with SSB-5125-66



All platforms feature full height internal support channels with flow-through vents.

Forkliftable Models

- Four-way fork entry with 4" underclearance

	SUMP CAP.	DIMENSIONS W x L x H	Model No.	Ship Wt.	Capacity Lbs. UDL
2-Drum	33 gal.	51 x 26 x 10.5	SST-5125	138	2000
2-Drum	66 gal.	51 x 26 x 16	SST-5125-66	171	2000
4-Drum	66 gal.	51 x 51 x 10.5	SST-5151	259	4000
6-Drum	99 gal.	76 x 51 x 10.5	SST-5176	381	6000
Ramp*	—	33 x 42 x 10.5	SST-RAMP	95	1500

*Ramp not for use with SST-5125-66



4-Drum Forkliftable



6-Drum Forkliftable



**4-Drum Forkliftable
with Ramp**