

Linear Actuated Elevating Carts 24V DC STANDARD

Transport materials from workstation to workstation with ease. Platform is raised and lowered with an electric linear actuator for precise positioning. Linear actuator will not allow platform to drift down - a common problem with hydraulic carts.

Model *CART-400-LA* & *CART-400-D-LA* are powered with (2) 12V AGM batteries and features a bench top charger. Emergency stop button on control box is standard.

Model *CART-500-LA* & *CART-500-LA-PSS* is powered with lithium battery and features an on-board battery charger.

MODEL NUMBER	PLATFORM SIZE (W x L)	UNIFORM CAPACITY	LOWERED HEIGHT	RAISED HEIGHT	WEIGHT (POUND)
STEEL CONSTRUCTION					
CART-400-LA	23 ⁵ / ₈ " x 35 ¹ / ₂ "	400 lb.	15"	34"	225
CART-400-D-LA	23 ⁵ / ₈ " x 35 ¹ / ₂ "	400 lb.	15"	50"	310
CART-500-LA	19 ¹ / ₂ " x 32"	500 lb.	15"	33"	248
PARTIALLY STAINLESS STEEL CONSTRUCTION					
CART-500-LA-PSS	19 ¹ / ₂ " x 32"	500 lb.	15"	33"	248

Adjustable Pallet Stands

The Adjustable Height Pallet Stands are designed to manually adjust to three different ergonomic working heights. Unit includes a three position manual adjusting bar with spring assist to help raise and lower the deck. The Pallet Stand must be empty when adjusting the height. Unit is welded steel construction with baked-in powder-coated tough finish. The optional bolt-on manual carousel, suffix CA, is 40" in diameter by 2" tall and rotates 360°. The caster feature, suffix CK, consists of 6" x 2" glass-filled nylon two (2) rigid and two (2) swivel casters with brake.

MODEL NUMBER	PLATFORM SIZE (W x L)	UNIFORM CAPACITY	LOWERED HEIGHT	FIRST SETTING	SECOND SETTING	THIRD SETTING	WEIGHT (POUND)
PS-4045	40" x 42 ¹ / ₄ "	5,000 lb.	10"	20 ¹ / ₄ "	30 ¹ / ₂ "	35 ¹ / ₄ "	253
PS-4045/CA	40" x 42 ¹ / ₄ "	4,000 lb.	12 ¹ / ₄ "	22 ¹ / ₄ "	32 ³ / ₄ "	37 ¹ / ₄ "	312
PS-4045/CA-CK	40" x 42 ¹ / ₄ "	1,500 lb.	19 ¹ / ₁₆ "	29 ¹ / ₁₆ "	39 ⁵ / ₁₆ "	45 ¹ / ₁₆ "	333
PS-4045-CK	40" x 42 ¹ / ₄ "	1,500 lb.	17 ¹ / ₂ "	27 ¹ / ₁₆ "	37 ⁵ / ₁₆ "	43 ¹ / ₁₆ "	271
PS-RF-CK	Casters to retro onto existing pallet stands						57

Die Tables

Designed to reduce back injuries and cumulative trauma disorders. Lifts heavy equipment to ergonomic working height. Manually operated hydraulic foot pump and lift cylinder. All welded steel construction will provide years of service and hard work. Small frame size allows unit to access hard-to-reach locations. Two (2) rigid and two (2) swivel casters with side brake standard. Suffix "C" stands for chrome top platform on foot pump operated models.

MODEL NUMBER	PLATFORM SIZE (W x L)	UNIFORM CAPACITY	SERVICE RANGE	POWER	WEIGHT (POUND)
DIE-2430-36	24" x 30"	2,000 lb.	24" to 36"	FOOT PUMP	290
DIE-2430-48	24" x 30"	2,000 lb.	30" to 48"	FOOT PUMP	295
DIE-2430-60	24" x 30"	2,000 lb.	36" to 60"	FOOT PUMP	344
DIE-2430-36-C	24" x 30"	2,000 lb.	24 ¹ / ₂ " x 36"	FOOT PUMP	290
DIE-2430-48-C	24" x 30"	2,000 lb.	30 ¹ / ₂ " x 48"	FOOT PUMP	295
DIE-2430-60-C	24" x 30"	2,000 lb.	36 ³ / ₄ " x 60 ³ / ₄ "	FOOT PUMP	344
DIE-2430-DC-C*	24" x 30"	2,000 lb.	24" to 51"	DC POWERED	463

*ONE (1) 12V BATTERY

Air Hydraulic Post Tables

Air Hydraulic Post Tables are great in manufacturing or distribution facilities when space is limited. The single speed foot pump and hand held push button control (reciprocating air/oil power) raise platform to the desired location. The foot pump can be utilized to maneuver the table height to a precise position. The unit requires a minimum hose diameter of 1/4" and air pressure of 72 to 100 PSI.

MODEL NUMBER	PLATFORM SIZE (W x L)	SERVICE RANGE	UNIFORM CAPACITY	WEIGHT (POUND)
HT-10-2036A-AIR	20" x 36"	36" to 54"	1,000 lb.	276
HT-20-2436A-AIR	24" x 36"	36" to 54"	2,000 lb.	367
HT-20-3036A-AIR	30" x 36"	36" to 54"	2,000 lb.	411

48 Hours
to Ship

model
CART-400-LA



model
CART-500-LA

model
CART-500-LA-PSS




POWDER
COATED
TOUGH



model
PS-4045-CK



48 Hours
to Ship



model
PS-4045/CA

YouTube

model
PS-RF-CK



model
DIE-2430-60-C

48 Hours
to Ship



model
DIE-2430-48



model
DIE-2430-DC-C



model
HT-10-2036A-AIR