## **Hydraulic Post Tables**

Hydraulic Post Tables are ideal in material handling facilities. The unit can be of use in a variety of environments from lifting dies and castings to moving machine parts. The corner posts are telescoping to help stabilize and fully support the load during operation. The tables roll smoothly on two (2) locking swivel casters with brakes and two (2) rigid. The tables can be lifted/lowered with a single speed foot pump, two-speed foot pump, or a two speed auto shifter that automatically shifts when the table is loaded. DC units include one (1) 12V battery to raise and lower the platform. They also include a battery, on-board charger, and a hand control on an 8 ft. coil cord. \*PP stands for poly-on-poly casters. PS = poly-on-steel casters. PP = polypropylene casters. Model HT-02-1616A and HT-03-1616A includes a platform that swivels 360° for use as a turntable. Model HT-02-1616A, HT-03-1616A and HT-05-1818A standard with a removable rubber platform cover.

Partially Stainless Steel Post Tables feature a zinc plated pump assembly and leg posts while the platform, base frame, handle, casters rigs, and hardware are stainless steel.

	model HT-03-1616A	-1818A	mode HT-10	I -2036A	model HT-20-2436A	model HT-20-3036A	model HT-20-3248
model HT-30-2436	model HT-30-3036	model HT-60-2436		model HT-20-2436-	DC model PT12-10	model HT-02-1616A-PSS	model HT-20-2436A-PSS
MODEL		UNIFORM	SERVICE	NUMBER	CASTER		WEIGHT
NUMBER STEEL CONSTRUC	SIZE (W x L)	CAPACITY	RANGE	OF POSTS	SIZE/TYPE*	OPERATION	(POUND)
HT-02-1616A@	16" x 16"	200 lb.	31" to 49"	0	4" x 1¼" PP	1-SPEED FOOT PUN	/IP 126
HT-03-1616A®	16" x 16"	300 lb.	31" to 49"	õ	4" x 1¼" PP	1-SPEED FOOT PUN	
HT-05-1818A®	18" x 18"	500 lb.	31" to 49"	2	4" x 1¼" PP	1-SPEED FOOT PUN	
HT-10-2036A®	20" x 36"	1,000 lb.	36" to 54"	2	5" x 1½" PS	2-SPEED FOOT PUN	/IP 241
HT-20-2436A®	24" x 36"	2,000 lb.	36" to 54"	4	5" x 1½" PS	2-SPEED FOOT PUN	
HT-20-3036A®	30" x 36"	2,000 lb.	36" to 54"	4	5" x 1½" PS	2-SPEED FOOT PUN	
HT-20-3042®	30" x 42"	2,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	2-SPEED AUTO-SHI	
HT-20-3248®	32" x 48"	2,000 lb.	36" to 54"	4	4" x 2" PHENOLIC 4" x 2" PHENOLIC	2-SPEED AUTO-SHI	
HT-20-4048 HT-20-4848	40" x 48" 48" x 48"	2,000 lb. 2,000 lb.	36" to 54" 36" to 54"	4 4	4 x 2" PHENOLIC 4" x 2" PHENOLIC	2-SPEED AUTO-SHI 2-SPEED AUTO-SHI	
HT-30-2436®	24" x 36"	3,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	2-SPEED AUTO-SHI	
HT-30-3036®	30" x 36"	3,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	2-SPEED AUTO-SHI	
HT-30-3042®	30" x 42"	3,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	2-SPEED AUTO-SHI	
HT-30-3248	32" x 48"	3,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	2-SPEED AUTO-SHI	
HT-30-4048	40" x 48"	3,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	2-SPEED AUTO-SHI	FT 540
HT-30-4848	48" x 48"	3,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	2-SPEED AUTO-SHI	
HT-40-2436⊛	24" x 36"	4,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	2-SPEED AUTO-SHI	
HT-40-3036®	30" x 36"	4,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	2-SPEED AUTO-SHI	
HT-40-3042®	30" x 42"	4,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	2-SPEED AUTO-SHI	
HT-40-3248	32" x 48"	4,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	2-SPEED AUTO-SHI	
HT-40-4048 HT-40-4848	40" x 48" 48" x 48"	4,000 lb. 4,000 lb.	36" to 54" 36" to 54"	4 4	4" x 2" PHENOLIC 4" x 2" PHENOLIC	2-SPEED AUTO-SHI 2-SPEED AUTO-SHI	
HT-60-2436®	24" x 36"	6.000 lb.	36" to 54"	4	6" x 2½" PHENOLIC	2-SPEED AUTO-SHI	
HT-60-3248®	32" x 48"	6,000 lb.	36" to 54"	4	6" x 2½" PHENOLIC	2-SPEED AUTO-SHI	
HT-60-4048	40" x 48"	6,000 lb.	36" to 54"	4	6" x 2½" PHENOLIC	2-SPEED AUTO-SHI	
HT-60-4848	48" x 48"	6,000 lb.	36" to 54"	4	6" x 21/2" PHENOLIC	2-SPEED AUTO-SHI	FT 596
HT-20-2436-DC	24" x 36"	2,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	12V DC POWER	396
HT-20-3036-DC	30" x 36"	2,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	12V DC POWER	425
HT-40-2436-DC	24" x 36"	4,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	12V DC POWER	501
HT-40-3248-DC	32" x 48" 24" x 36"	4,000 lb.	36" to 54"	4	4" x 2" PHENOLIC	12V DC POWER	555
HT-60-2436-DC HT-60-3248-DC	24 x 30 32" x 48"	6,000 lb. 6.000 lb.	36" to 54" 36" to 54"	4 4	6" x 2½" PHENOLIC 6" x 2½" PHENOLIC	12V DC POWER 12V DC POWER	558 625
LOW PROFILE STEEL CONSTRUCTION							
PT12-10®	20" x 30"	1,000 lb.	25" to 37"	2	5" x 1½" PS	1-SPEED FOOT PUN	/IP 184
PT12-20®	24" x 36"	2.000 lb.	25" to 37"	4	5" x 1½" PS	1-SPEED FOOT PUN	
PT12-40®	24" x 36"	4,000 lb.	25" to 37"	4	5" x 1½" PS	1-SPEED FOOT PUN	
PT2436E®	24" x 36"	1,000 lb.	34" to 52"	4	5" x 1½" PS	LINEAR ACTUATED	250
PARTIALLY STAINLESS STEEL CONSTRUCTION							
HT-02-1616A-P		200 lb.	31" to 49"	0	4" x 1¼" PP	1-SPEED FOOT PUN	
HT-05-1818A-P		500 lb.	31" to 49"	2	4" x 1¼" PP	1-SPEED FOOT PUN	
HT-10-2036A-P		1,000 lb.	36" to 54"	2	4" x 1½" PP	2-SPEED FOOT PUN	
HT-20-2436A-P		2,000 lb.	36" to 54"	4 4	5" x 1½" PP	2-SPEED FOOT PUN	
HT-20-3036A-P	SS⊛ 30" x 36"	2,000 lb.	36" to 54"	4	5" x 1½" PP	2-SPEED FOOT PUN	010

LOW PROFILE & SHORT PUMP LIFT RANGE AVAILABLE. CONSULT FACTORY. AC, DC, LINEAR ACTUATED or AIR/OIL AVAILABLE. MODEL NUMBERS WITH THE SUFFIX "A" ARE SHIPPED KNOCK-DOWN 48 Hours

YouTube

New