



Heavy Duty Guard Rails

Heavy Duty Guard Rails are one of the strongest on the market withstanding multiple hits from a forklift. Stops a 12,000 lb. forklift traveling at 8 mph. Upon impact, guard rail distributes the shock throughout the entire section, resulting in zero deflection. Heavy duty pipe sleeved in durable HDPE plastic, where pipe post is 4" schedule 80 pipe, and pipe rail is 6" schedule 40 pipe. Standard color is safety yellow. The maintenance-free, never paint again system will keep your facility looking clean and new. Units arrive fully assembled. Other configurations and sizes available, contact factory.

MODEL Number	OVERALL Length	OVERALL Height	BASE PLATE (W x L)	WEIGHT (POUND)
HDGR-4-27	48"	27"	10" x 10"	299
HDGR-4-36	48"	36"	10" x 10"	321
HDGR-4-42	48"	42"	10" x 10"	336
HDGR-6-27	72"	27"	10" x 10"	387
HDGR-6-36	72"	36"	10" x 10"	409
HDGR-6-42	72"	42"	10" x 10"	424
HDGR-8-27	96"	27"	10" x 10"	475
HDGR-8-36	96"	36"	10" x 10"	497
HDGR-8-42	96"	42"	10" x 10"	512
HDGR-10-27	120"	27"	10" x 10"	563
HDGR-10-36	120"	36"	10" x 10"	585
HDGR-10-42	120"	42"	10" x 10"	600
HDGR-12-27	144"	27"	10" x 10"	651
HDGR-12-36	144"	36"	10" x 10"	673
HDGR-12-42	144"	42"	10" x 10"	688
AS-346⊛	ANCHOR BOLTS FOR CONCRETE (1) 3/4" x 6"			1
AS-346-4PK®	ANCHOR BOLTS FOR CONCRETE (4) 3/4" x 6"			4









Steel Pipe Safety Bollards

Bollards can be used both indoors and outdoors to protect work areas, racking and personnel. Plastic top caps are removable on the $1\frac{3}{4}$ ", $4\frac{1}{2}$ ", and $5\frac{1}{2}$ " diameter units and bollard may be filled with concrete. Steel caps are welded on the $6\frac{5}{8}$ " and $8\frac{5}{8}$ " diameter units. Base plate includes four (4) pre-drilled mounting holes. Mounting kits and replacement caps available. Baked-in powder-coated toughness.

MODEL			OUTSIDE	BASE PLATE	WEIGHT
NUMBER	FINISH	HEIGHT	DIAMETER	(W x L)	(POUND)
BOL-24-2®	YELLOW POWDER COAT	24"	1¾"	4" x 4"	6
BOL-36-2®	YELLOW POWDER COAT	36"	1¾"	4" x 4"	9
BOL-42-2®	YELLOW POWDER COAT	42"	1¾"	4" x 4"	10
BOL-48-2®	YELLOW POWDER COAT	48"	13/4"	4" x 4"	11
BOL-24-4.5®	YELLOW POWDER COAT	24"	4½"	8" x 8"	17
BOL-36-4.5®	YELLOW POWDER COAT	36"	4½"	8" x 8"	22
BOL-42-4.5®	YELLOW POWDER COAT	42"	4½"	8" x 8"	26
BOL-48-4.5®	YELLOW POWDER COAT	48"	4½"	8" x 8"	29
BOL-62-4.5	YELLOW POWDER COAT	62"	4½"	8" x 8"	39
BOL-72-4.5	YELLOW POWDER COAT	72"	4½"	8" x 8"	49
BOL-24-5.5®	YELLOW POWDER COAT	24"	5½"	8" x 8"	20
BOL-36-5.5®	YELLOW POWDER COAT	36"	5½"	8" x 8"	26
BOL-42-5.5®	YELLOW POWDER COAT	42"	5½"	8" x 8"	30
BOL-48-5.5®	YELLOW POWDER COAT	48"	5½"	8" x 8"	35
BOL-62-5.5	YELLOW POWDER COAT	62"	5½"	8" x 8"	45
BOL-72-5.5	YELLOW POWDER COAT	72"	5½"	8" x 8"	55
BOL-36-6.5	YELLOW POWDER COAT	36"	65/8"	8" x 8"	30
BOL-42-6.5	YELLOW POWDER COAT	42"	65/8"	8" x 8"	49
BOL-48-6.5	YELLOW POWDER COAT	48"	65/8"	8" x 8"	51
BOL-62-6.5	YELLOW POWDER COAT	62"	65/8"	8" x 8"	61
BOL-72-6.5	YELLOW POWDER COAT	72"	65/8"	8" x 8"	71
BOL-36-8.5	YELLOW POWDER COAT	36"	85/8"	10" x 10"	53
BOL-42-8.5	YELLOW POWDER COAT	42"	85/8"	10" x 10"	62
BOL-48-8.5	YELLOW POWDER COAT	48"	85/8"	10" x 10"	126
AS-383®	ANCHOR BOLTS FOR CONC	RETE (1) 3/	8" x 3" (1 ³ / ₄ " UNI	TS)	1
AS-383-4PK®	ANCHOR BOLTS FOR CONCRETE (4) 3/8" x 3" (13/4" UNITS)			4	
AS-344®	ANCHOR BOLTS FOR CONCRETE (1) 3/4" x 4" (OTHER UNITS)			1	
AS-344-4PK®	ANCHOR BOLTS FOR CONCRETE (4) 3/4" x 4" (OTHER UNITS)			4	

Replaceable Bollard Caps

Replace lost or damaged bollard caps. Easy to attach. Plastic cap has serrated tapered teeth for press-fit installation.

MODEL Number	MATERIAL	INNER DIAMETER PIPE FITTING	FITS Model	WEIGHT (POUND)
BOL-CAP-1.75-P®	PLASTIC	1.38" (11/4" SCH. 40 PIPE)	BOL-2	2
BOL-CAP-4.5-P _☉	PLASTIC	4.26" (4" SCH. 10 PIPE)	BOL-4.5	2
BOL-CAP-5.5-P _☉	PLASTIC	5.30" (5" SCH. 10 PIPE)	BOL-5.5	2
BOL-CAP-1.75-R⊙	RUBBER	1.38" (11/4" SCH. 40 PIPE)	BOL-2	2
BOL-CAP-5.5-R⊙	RUBBER	5.30" (5" SCH. 10 PIPE)	BOL-5.5	2





PLASTIC series BOL-CAP-P





RUBBER series BOL-CAP-R

Protective Dome Covers for Bollards

Prevent accidents and injuries from people tripping over raised bolts. Easy to use device slides over bollards covering mounting hardware and base plate for a nice clean finish. Durable yellow baked-in powder-coated toughness. Steel construction. No hardware required.

MODEL Number	USE WITH	OUTSIDE Diameter	HEIGHT	WEIGHT (POUND)
DOME-4.5 [®]	41/2" DIAMETER BOLLARDS	14"	213/16"	8
DOME-5.5 [®]	5½" DIAMETER BOLLARDS	14"	2¾"	9



Special Powder Coat Finishes for Guards & Barriers

Now you can select from a variety of colors to fit many different types of bollard installations. Color codes can quickly identify different areas in a factory. For example use red to signal fire extinguishers. To complete your buildings appearance choose from our architectural color palette. Simply add the "SPO" number to your product number and contact factory for current pricing.

MODEL Number	DESCRIPTION	COLOR	GLOSS Level
ARCHITECTURAL COLORS	S		
SPO-PC-BRN-EB	EARTH BROWN	DARK BROWN	85%
SPO-PC-BRN-KT	KHAKI TAN	MEDIUM BEIGE	85%
SPO-PC-BRN-SB	SANDY BEIGE	LIGHT BEIGE	85%
SPO-PC-BLK-HG	BLACK, HIGH GLOSS	BLACK, HIGH GLOSS	85%
SPO-PC-BLK-SG	BLACK, SEMI-GLOSS	BLACK, SEMI-GLOSS	35%
SPO-PC-GRN-H	HUNTER GREEN	DARK GREEN	85%
SPO-PC-GRN-T	TRACTOR GREEN	MEDIUM GREEN	85%
SPO-PC-GY-SG	BATTLE SHIP GRAY	MEDIUM GRAY	85%
SPO-PC-GY-MG	MACHINE GRAY	LIGHT GRAY	85%



















DARK BROWN





DARK GREEN



MEDIUM



MODEL			GLOSS
NUMBER	DESCRIPTION	COLOR	LEVEL
BRIGHT/ALERT COLOR	S		
SPO-PC-WT	SNOWY WHITE	WHITE	85%
SPO-PC-SR	SODA RED	RED	85%
SPO-PC-ORG-C	CITRUS ORANGE	ORANGE	85%
SPO-PC-BL-E	ERGO BLUE	VESTIL BLUE	85%
SPO-PC-BG	BUBBLE GUM	PINK	85%

