

Structural Rack Guards

Economical way to protect against damage to pallet racking and wall corners. Constructed of 6" or 8" cast steel for durability. Available with or without a rubber bumper. Easy to install to concrete surface. Four mounting holes for maximum stability. Safety yellow baked-in powder-coated toughness. Models G6 require 1/2" anchor bolts. Models G8 require 3/4" anchor bolts. Installation hardware sold separately.

MODEL NUMBER	OVERALL HEIGHT	USABLE OPENING (W x D)	OVERALL BASE (W x D)	WEIGHT (POUND)
STRUCTURAL RACK GUARDS				
G6-12	12¼"	4 ⁹ / ₁₆ " x 3 ¹¹ / ₁₆ "	8 ¹ / ₁₆ " x 6"	12
G6-18	18¼"	4 ⁹ / ₁₆ " x 3 ¹¹ / ₁₆ "	8 ¹ / ₁₆ " x 6"	16
G6-24	24¼"	4 ⁹ / ₁₆ " x 3 ¹¹ / ₁₆ "	8 ¹ / ₁₆ " x 6"	22
G6-36	36¼"	4 ⁹ / ₁₆ " x 3 ¹¹ / ₁₆ "	8 ¹ / ₁₆ " x 6"	31
G8-12	12¼"	6 ⁹ / ₁₆ " x 3 ¹¹ / ₁₆ "	10 ¹ / ₁₆ " x 6"	13
G8-18	18¼"	6 ⁹ / ₁₆ " x 3 ¹¹ / ₁₆ "	10 ¹ / ₁₆ " x 6"	21
G8-24	24¼"	6 ⁹ / ₁₆ " x 3 ¹¹ / ₁₆ "	10 ¹ / ₁₆ " x 6"	28
G8-36	36¼"	6 ⁹ / ₁₆ " x 3 ¹¹ / ₁₆ "	10 ¹ / ₁₆ " x 6"	37
STRUCTURAL RACK GUARDS WITH RUBBER BUMPERS				
G6-12-B	12¼"	4 ⁹ / ₁₆ " x 2 ⁷ / ₈ "	8 ¹ / ₁₆ " x 6"	19
G6-18-B	18¼"	4 ⁹ / ₁₆ " x 2 ⁷ / ₈ "	8 ¹ / ₁₆ " x 6"	25
G6-24-B	24¼"	4 ⁹ / ₁₆ " x 2 ⁷ / ₈ "	8 ¹ / ₁₆ " x 6"	42
G6-36-B	36¼"	4 ⁹ / ₁₆ " x 2 ⁷ / ₈ "	8 ¹ / ₁₆ " x 6"	44
G8-12-B	12½"	6 ⁹ / ₁₆ " x 2 ¹¹ / ₁₆ "	10 ¹ / ₁₆ " x 6"	23
G8-18-B	18½"	6 ⁹ / ₁₆ " x 2 ¹¹ / ₁₆ "	10 ¹ / ₁₆ " x 6"	38
G8-24-B	24½"	6 ⁹ / ₁₆ " x 2 ¹¹ / ₁₆ "	10 ¹ / ₁₆ " x 6"	51
G8-36-B	36½"	6 ⁹ / ₁₆ " x 2 ¹¹ / ₁₆ "	10 ¹ / ₁₆ " x 6"	53
AS-125	ANCHOR BOLTS FOR CONCRETE (1) 1/2" x 5" (G6 UNITS)			1
AS-125-4PK	ANCHOR BOLTS FOR CONCRETE (4) 1/2" x 5" (G6 UNITS)			4
AS-344	ANCHOR BOLTS FOR CONCRETE (1) 3/4" x 4" (G8 UNITS)			1
AS-344-4PK	ANCHOR BOLTS FOR CONCRETE (4) 3/4" x 4" (G8 UNITS)			4



Low Profile Rack Guards

Protect pallet racking and wall corners against damage from fork trucks, pallet trucks, and carts with Low Profile Rack Guards. All components are laser cut. Quick and easy two (2) hole installation. Installs in half the time of other guards. Safety yellow baked-in powder-coated toughness. Steel construction. Installation hardware sold separately.

MODEL NUMBER	OVERALL HEIGHT	USABLE OPENING (W x D)	OVERALL BASE (W x D)	WEIGHT (POUND)
NPG4-12	11 ⁷ / ₈ "	4¼" x 1"	8" x 3"	5
NPG4-18	17 ⁷ / ₈ "	4¼" x 1"	8" x 3"	7
NPG4-24	23 ⁷ / ₈ "	4¼" x 1"	8" x 3"	9
NPG4-36	35 ⁷ / ₈ "	4¼" x 1"	8" x 3"	15
NPG6-12	11 ⁷ / ₈ "	6¼" x 1"	10" x 3"	7
NPG6-18	17 ⁷ / ₈ "	6¼" x 1"	10" x 3"	8
NPG6-24	23 ⁷ / ₈ "	6¼" x 1"	10" x 3"	11
NPG6-36	35 ⁷ / ₈ "	6¼" x 1"	10" x 3"	16
AS-125	ANCHOR BOLTS FOR CONCRETE (1) 1/2" x 5"			1
AS-125-4PK	ANCHOR BOLTS FOR CONCRETE (4) 1/2" x 5"			4



Corner Guards

Protect busy corners, expensive machinery, and personnel with 90° perpendicular protection. "SAFETY FIRST" promotion reminds personnel of the number one priority. Steel units include baked-in powder-coated toughness. Aluminum unit is unfinished. Installation hardware sold separately.



MODEL NUMBER	OVERALL HEIGHT	OVERALL LENGTH	SIDE HEIGHT	MATERIAL	WEIGHT (POUND)
PCG-16	16"	16"	8"	STEEL	26
PCG-16-A	16"	16"	8"	ALUMINUM	8
PCG-24	24"	24"	12¼"	STEEL	59
PCG-24-A	24"	24"	12"	ALUMINUM	10
AS-344	ANCHOR BOLTS FOR CONCRETE (1) 3/4" x 4"				1
AS-344-4PK	ANCHOR BOLTS FOR CONCRETE (4) 3/4" x 4"				4

