Upright Panel Movers

Models TF, TH, TG, TY - Versatile transporter for material moved on its edge

1,200 LB CAPACITY



Model TF Shown

1,200 LB CAPACITY



Model TH Shown

1,200 LB CAPACITY



Model TG Shown

2,000 LB CAPACITY



Model TY Shown

Product Features:

- · All welded frame construction.
- Durable steel frame with 3 sockets on each end.
- 3 removable 1-1/4" tubular dividers with smooth radius bend 27" high.
- Load space between dividers -12"
- · Bolt on casters, for easy replacement.
- Platform height Model TF 8", Model TH 9", Model TG & TY 10".
 Overall height 35" (Models TF, TH & TG), 36" (Model TY).
- · Powder coated gray finish ONLY.

Other Specifications:

Model TF

• 5" x 1-1/4" urethane swivel casters.

Model TH

- Includes 3/4" wood deck.
- 5" x 1-1/4" urethane swivel casters.

Model TG

- Includes 2 carpeted 2" x 3" wood rails.
- 5" x 1-1/4" urethane swivel casters.

Model TY

- Includes 12 gauge flush deck.
- 5" x 2" urethane swivel casters.

Model TF - Steel Frame

WxL	5" Casters	Ship Wgt.	
(in)	Urethane	(lbs)	
28 x 31	TF831-U5-AS		

Model TH - Steel Frame, Wood Capped

WxL	5" Casters	Ship Wgt.	
(in)	Urethane	(lbs)	
28 x 31	TH831-U5-AS	75	

Model TG - Steel Frame, Carpeted Rails

WxL	5" Casters	Ship Wgt.		
(in)	Urethane	(lbs)		
28 x 31	TG831-U5-AS			

Model TY - Steel Deck

WxL	5" Casters	Ship Wgt.	
(in)	Urethane	(lbs)	
28 x 31	TY831-U7-AS		

BOXED TO SHIP FED EX GROUND

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" \times 3" \times 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic
- Rubber
- Polyurethane
- Thermorubber
- · Steel (semi)
- Full Pneumatic
- Semi Pneumatic

Brakes

Code

N8

N1

Z8

Code

MP

MS

Size (in)

8 x 3

12 x 4

Size (in)

8 x 2-1/2

8 x 2-1/2

8 x 3

Pattern (in)

Pattern (in)

3 x 3

3 x 3

3 x 3

3 x 3

3 x 3

Duty Series

- Wing Brakes (Toe)
- Floor Lock

- Best rollability, high strength, hardest material.
- Best if floor has debris, quieter roll.
- Best if floor conditions vary, non-marking.
- Gray non-marking, soft rubber for quietest roll and best floor protection.
- High shock and impact resistant.
- Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Same as full pneumatic without maintenance of air.
- On swivel casters only, must be ordered with caster.
- Mount is welded in place, makes models not returnable.

Floor Lock



4 Series





Urethane Thermorubber 5 Series





Urethane Thermorubbe



Steel 7, 6, & 8 Series





Phenolic Mold Or Rubber





Urethane

Thermorubber



Steel N Series





Full Pneumatic

Semi Pneumatic

Mill Duty Series





Phenolic

Steel

• FIOUR LOCK		- Mount is weld	- Mount is welded in place, makes models not returnable.				
4 Series———————————————————————————————————							
	01100	Bolt Hole			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	Bearing	(set of 4)	Locks	Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1.200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4
5.5	Series—						
5 0		Bolt Hole			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	Bearing	<u>(set of 4)</u>	Locks	Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5
7 S	eries—		,		,		
, ,		Bolt Hole			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	Bearing	<u>(set of 4)</u>	Locks	Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7
6 S	eries—		` '				
		Bolt Hole			Capacity	Floor	Brake
<u>Code</u>	Size (in)	Pattern (in)	Wheel Material	<u>Bearing</u>	(set of 4)	<u>Locks</u>	<u>Locks</u>
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6
8 Series — The ser							
		Bolt Hole	Wheel Meterial	Desilve	Capacity	Floor	Brake
Code	Size (in)	Pattern (in)	Wheel Material	<u>Bearing</u>	(set of 4)	<u>Locks</u>	<u>Locks</u>
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8
N S	Series –	Dalk Hala			O-mark.	Floor	Dueles
		Bolt Hole			Capacity	Floor	Brake

Wheel Material

Full Pneumatic

Full Pneumatic

Wheel Material

Phenolic

Steel

Semi Pneumatic

Bearing

Bearing

Roller

Ball

Ball

Ball

Ball

(set of 4)

1,200 lbs

2,200 lbs

2.000 lbs

Capacity

(set of 4)

7,000 lbs

7,000 lbs

Locks

FN

N/A

F8

Floor

Locks

ML

ML

Locks

BN

N/A

BN

Brake

Locks

BM

BM