



## Security Box Truck

1200 lbs. to 3600 lbs. Capacity

Heavy-duty all-welded 1-1/2" angle frame with 13 gauge expanded metal panels provide a durable truck to secure and transport your materials or cargo. Expanded metal sides and top allows easy visibility of contents. Double-hinged top cover has padlock hasp for added security. Front drop-gate with spring latches provide easy access. Interior height - 36". Choose wheels based on rolling surface and capacity required. Available in 6" non-marking polyurethane, 9" pneumatic, and 10" solid rubber.



Model SB-2448-10SR



Model SB-2448-6PY

	6" x 2" POLYURETHANE 3600 lbs. Capacity 47" OAH		9" x 3" PNEUMATIC 1200 lbs. Capacity 51" OAH		10" x 2-3/4" SOLID RUBBER 1500 lbs. Capacity 51-1/2" OAH	
Deck Size	Model No.	Wt.	Model No.	Wt.	Model No.	Wt.
24 x 48	SB-2448-6PY	173	SB-2448-9P	176	SB-2448-10SR	185
24 x 60	SB-2460-6PY	195	SB-2460-9P	198	SB-2460-10SR	207
30 x 48	SB-3048-6PY	196	SB-3048-9P	199	SB-3048-10SR	208
30 x 60	SB-3060-6PY	220	SB-3060-9P	223	SB-3060-10SR	232

## Security Box Truck with Solid Sides

Heavy-duty all-welded 1-1/2" angle frame with 14 gauge all-welded steel construction protects your items from view and offers complete security. Drop gate front permits easy access to contents. User friendly double hinge cover folds down and back. Padlock hasp provides extra security. Interior height of 36". For rolling over smooth surfaces choose the 6" x 2" mold-on rubber wheels. For rolling over rough surfaces the 10" solid rubber version is the perfect choice.



Model SBS-2448-10SR



Model SBS-2448-6MR

	6" x 2" MOLD-ON RUBBER 2000 lbs. Capacity		10" x 2-3/4" SOLID RUBBER 1500 lbs. Capacity	
Deck Size	Model No.	Wt.	Model No.	Wt.
24 x 48	SBS-2448-6MR	272	SBS-2448-10SR	284
30 x 60	SBS-3060-6MR	349	SBS-3060-10SR	361



## Wheel Selection Guide

### Polyurethane Wheels

**Load Capacity Range:**  
300 – 1,000 lbs.



**Characteristics:** Easier rolling for higher capacities, long lasting, chemical resistant, non-marking and quiet operation.

High strength polyurethane tread liquid cast and mechanically locked to a polymer or cast metal core. A polyurethane tread is superior for industrial, warehouse and institutional applications with a great combination of easy rolling and maneuverability under heavy load capacity while able to quietly roll over rough floor surfaces.

### Phenolic Wheels

**Load Capacity Range:**  
900 – 1,250 lbs.



**Characteristics:** Best rolling for heavy load capacities, long lasting, chemical resistant, high temperature, non-marking for smooth floor surface.

A solid one piece wheel that is high pressure molded with reinforced fiber-filled phenolic resin. A cost effective wheel best used for high capacity industrial and warehouse applications. Hard tread wheel offers the least rolling resistance on smooth floors, but does not absorb vibration over rough surfaces.

### Mold-On Rubber Wheels

**Load Capacity Range:**  
500 – 600 lbs.



**Characteristics:** Better load capacity, long lasting, cushion tread, absorbs shock and vibration, floor protection and quiet operation.

Rubber tread vulcanized to metal core. A good combination of load capacity and cushion tread that easily and quietly rolls over rough floors. A great wheel choice for heavy industrial and warehouse applications.

### Solid Rubber Wheels

**Load Capacity Range:**  
300 – 400 lbs.



**Characteristics:** Good load capacity, great for rough floor surfaces, puncture-proof, floor protection and quiet operation.

Cushioned rubber tire over plastic hub that is more stable and easier to roll under heavy loads than pneumatic wheels. Sometimes referred to as a semi-pneumatic tire, these wheels are a rugged, maintenance-free (no air pressure to fill and maintain) and are an alternative to pneumatic wheels.

### Pneumatic Wheels

**Load Capacity Range:**  
300 – 400 lbs.



**Characteristics:** Great cushion ride over rough floor surfaces, best option for traveling over small obstructions or outdoor applications. Best shock and vibration absorption.

Like an automotive tire, an air filled rubber tire on a metal hub is able to easily roll over uneven surfaces and bumps but does require air pressure management. Under heavy loads, the pneumatic tire profile will compress creating greater rolling resistance. Pneumatic wheels are ideal for handling fragile loads over rough surfaces.

### Flat Free Hand Truck Wheels

**Load Capacity Range:**  
300 lbs.



**Characteristics:** All of the benefits of a pneumatic wheel without losing air or going flat. This non-marking tire is composed of a dense microcellular polyurethane foam that performs like a pneumatic tire, cushioning the load and rolling over rough surfaces more easily. Upgraded precision ball bearing improves rollability and extends life.

## Wheel Specifications

Wheel Dia.	Tread Width	Wheel Type	Bearing I.D.	Centered Hub Model No.	Bearing I.D.	Offset Hub Model No.
5	1-1/4	Polyurethane	3/8" Ball	WHMP-05114		
6	2	Mold-On Rubber Polyurethane Phenolic	Roller	WHMS-0620 WHMP-0620 WHPL-0620		
8	2	Mold-On Rubber Polyurethane Phenolic	Roller	WHMS-0820 WHMP-0820 WHPL-0820		
8	2-1/2	Solid Rubber	3/4" Ball	WHSP-0825	5/8" Ball	WHSP-0825-0
9	3	Pneumatic 2.80/2.50-4	5/8" Ball	WHPN-0830		
10	2-3/4	Solid Rubber	5/8" Ball	WHSP-1027P-C	5/8" Ball	WHSP-1027-P
10	3-1/2	Pneumatic 4.10/3.50-4	5/8" Ball	WHPN-1035-C	5/8" Ball	WHPN-1035
10	3-1/2	Flat Free 4.10/3.50-4 Microcellular Foam			5/8" Ball (Precision)	WHFF-1035
12	2-1/2	Mold-On Rubber	1" Roller	WHMS-12250		
12	3-1/2	Pneumatic 4.10/3.50-6 Pneumatic 4.10/3.50-6	5/8" Ball 1" Roller	WHPN-1235 WHPN-1235-RB		
16	4	Pneumatic 4.80/4.00-8	1" Roller	WHPN-1640		